

10K CAST STAINLESS STEEL BALL VALVE SCREWED ENDS

KITZ Fig: 10UT

Sizes: 21/2-inch(65-mm)

静電防止機構付,フルボア型

Standards

- . End to End: KITZ STANDARD
- . End Connection: JIS B0203
- . Wall Thickness: ASME B16.34 CLASS 150

Test Standard

- . KITZ STANDARD

Approvals

(一社) 日本バルブ工業会規格適合品 65-80 mm (21/2-3 inch)
approved



Dimensions



SIZE (inch/mm)	L	L1	H	D1	Kg
21/2 65	160.0		154.0	400.0	
3 80	182.0		163.0	400.0	

Specifications

10K CAST STAINLESS STEEL BALL VALVE SCREWED ENDS, 静電防止機構付,フルボア型

End to End : KITZ STANDARD, End Connection : JIS B0203, Wall Thickness : ASME B16.34 CLASS 150, Test Standard : KITZ STANDARD, Sizes : 21/2-inch(65-mm), Approvals : (一社) 日本バルブ工業会規格適合品 65-80 mm (21/2-3 inch), ,KITZ Fig : 10UT

JV



Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.

