20K DUCTILE IRON, SWING CHECK VALVES

KITZ Fig: 20S0B Sizes: 21/2-inch(65-mm) BOLTED COVER, FLANGED ENDS.

Standards

. End to End: JIS B2002

End Connection: JIS B2239 20KWall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Approvals

(一社) 日本バルブ工業会規格適合品 65-300 mm (21/2-12 inch) approved

Dimensions

SIZE(inch/mm)		L	L1	Н	D1	Kg
21/2	65	292.0		145.0		
3	80	318.0		160.0		
4	100	356.0		185.0		
5	125	400.0		220.0		
6	150	444.0		240.0		
8	200	533.0		275.0		
10	250	622.0		335.0		
12	300	711.0		370.0		




NAME OF PART	MATERIAL	SPECIFICATION	
BODY	DUCTILE IRON	FCD-S	
COVER	DUCTILE IRON	FCD-S	
DISC	STAINLESS STEEL	403SS	

Specifications

20K DUCTILE IRON, SWING CHECK VALVES, BOLTED COVER, FLANGED ENDS. End to End: JIS B2002, End Connection: JIS B2239 20K, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 21/2-inch(65-mm), Approvals: (一社) 日本バルブ工業会規格適合品65-300 mm (21/2-12 inch), BODYMATERIAL: DUCTILE IRON, COVERMATERIAL: DUCTILE IRON, DISCMATERIAL: STAINLESS STEEL, KITZ Fig: 20S0B



JV



For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



