20K DUCTILE IRON, WAFER TYPE CHECK VALVES

KITZ Fig: 20SWZ Sizes: 21/2-inch(65-mm)

Standards

. End to End: KITZ STANDARD

. End Connection: WAFER TYPE (JIS 20K)

. Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD Conform to

公共建築工事標準仕様書相当品(機械設備工事編) 65-450 mm (21/2-18

inch) approved

Dimensions

SIZE(inc	h/mm)	L	L1	Н	D1	Kg
21/2	65	60.0		150.0	70.0	
3	80	67.0		156.0	70.0	
4	100	68.0		169.0	70.0	
5	125	83.0		183.0	70.0	
6	150	95.0		216.0	80.0	
8	200	127.0		243.0	80.0	
10	250	140.0		290.0	90.0	
12	300	181.0		315.0	90.0	
14	350	184.0		330.0	90.0	
16	400	191.0		355.0	90.0	
18	450	204.0		388.0	90.0	

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
BODY	DUCTILE IRON+NBR	FCD-S+NBR	
STEM	BRASS	C3531(2)	

Specifications

20K DUCTILE IRON, WAFER TYPE CHECK VALVES


End to End : KITZ STANDARD, End Connection : WAFER TYPE (JIS 20K), Wall Tchickness : KITZ STANDARD, Test Standard : KITZ


STANDARD, Sizes : 21/2-inch(65-mm), Conform to : 公共建築工事標準仕 様書相当品(機械設備工事編) 65-450 mm (21/2-18 inch), BODYMATERIAL

:DUCTILE IRON+NBR, STEMMATERIAL :BRASS, KITZ Fig : 20SWZ









Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



