
TYPE 400 LEAD FREE CAST BRONZE ,BALL VALVES

KITZ Fig : CTLN
Sizes : 1/2～2inch(15～50mm)
LONG NECK,STANDARD BORE,SOLDER-JOINT ENDS.
Standards :
・End to End : KITZ STANDARD
・End Connection : ASME B16.18
・Wall Thickness : KITZ STANDARD
Test Standard : KITZ St'd-1
Approvals : 1/2～2inch(15～50mm)
Standards : 1/2～2inch(15～50mm)





Dimensions

SIZE(inch/mm)		L	H	D	Large Box Qty	Approx (kg)
1/2	15	58.0	75.0	80.0	10	0.3
3/4	20	73.0	79.0	80.0	8	0.4
1	25	88.0	83.0	110.0	8	0.7
11/4	32	99.0	98.0	110.0	6	1.1
11/2	40	114.0	102.0	110.0	4	1.4
2	50	135.0	109.0	140.0	2	2.2

Material

Part Name	Material	Remark
BODY	CAST BRONZE	CAC911
BODY CAP	CAST BRONZE	CAC911
STEM	SPECIAL BRASS (4)	
BALL	STAINLESS STEEL	SCS13A

Specifications

TYPE 400 LEAD FREE CAST BRONZE,BALL VALVES
End Connection : ASME B16.18,Sizes : 1/2～2inch(15～50mm),
BODYMaterial:CAST BRONZE, BODY CAPMaterial:CAST BRONZE,
STEMMaterial:SPECIAL BRASS (4), BALLMaterial:STAINLESS STEEL,KITZ Fig : CTLN

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.

© KITZ Corporation. All Right Reserved.